





DIRO SBL L 83 W

202 297 83 W

AVAILABLE IN

BLACK 202 297 83 B

WHITE 202 297 83 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 208
RECESSED DEPTH (MM)	70
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP43/20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 1050mA-DC INCL.PC SBL

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 17,5W / CRI>80 / 3000K / 3000lm
LED TECHNICS (LIGHT SOURCE)	3000 lm // 17 W // 171 lm/W
LED TECHNICS (LUMINAIRE)	1643lm // 20W // 82lm/W

For detailed installation instructions, please consult the manual: [202_297_XX_HAND.pdf](#)